

# CAPACITANCE TYPE LEVEL TRANSMITTER



## ELTRAN

ELTRAN 701 ABS : CONDUCTING LIQUID  
ELTRAN 702 ABS : NONCONDUCTING LIQUID  
ELTRAN 703 ALUMINIUM : CONDUCTING LIQUID  
ELTRAN 704 ALUMINIUM : NONCONDUCTING LIQUID



### TECHNICAL SPECIFICATION

MEASURING RANGE : 50 TO 2000 mm RUGGEDPROBE 2000 TO 10000 mm FLEXPBROBE  
TRANSMITTER TYPE : LOOP POWERED  
SUPPLY VOLTAGE : 12 TO 30 V DC  
OUT PUT : 4-20mA CONSTANT CURRENT  
MAXIMUM LOAD RESISTANCE : SUPPLY VOLTAGE - 12 V  $\Omega$   
0.02 A  
PRESSURE RATING : 6 Kg/cm<sup>2</sup>  
TEMPERATURE : -20 TO 100°C  
ENCLOSURE : DIE CAST ALUMINIUM DULY APPROVED FLAME PROOF  
ABS DULY APPROVED FOR IP 65/ 67  
RESOLUTION : 0.1mm  
ACCURACY :  $\pm 0.25$  % FSR

R-1 A,VILAS APPT, SANT TUKARAM  
PATH,KOPRI, THANE(E) 400 603,INDIA  
Fax: 91-22-2532 4845

**SPINK CONTROLS**®

Phone:91-22-2532 8223/24 Email:info@spinkcontrolsindia.com  
www.spinkcontrolsindia.com