

CAPACITANCE TYPE LEVEL TRANSMITTER



ELTRAN

ELTRAN 701 ABS : CONDUCTING LIQUID
ELTRAN 702 ABS : NONCONDUCTING LIQUID
ELTRAN 703 ALUMINIUM : CONDUCTING LIQUID
ELTRAN 704 ALUMINIUM : NONCONDUCTING LIQUID



TECHNICAL SPECIFICATION

MEASURING RANGE : 50 TO 2000 mm RUGGEDPROBE 2000 TO 10000 mm FLEXPBROBE
TRANSMITTER TYPE : LOOP POWERED
SUPPLY VOLTAGE : 12 TO 30 V DC
OUT PUT : 4-20mA CONSTANT CURRENT
MAXIMUM LOAD RESISTANCE : SUPPLY VOLTAGE - 12 V Ω
0.02 A
PRESSURE RATING : 6 Kg/cm²
TEMPERATURE : -20 TO 100°C
ENCLOSURE : DIE CAST ALUMINIUM DULY APPROVED FLAME PROOF
ABS DULY APPROVED FOR IP 65/ 67
RESOLUTION : 0.1mm
ACCURACY : ± 0.25 % FSR

R-1 A,VILAS APPT, SANT TUKARAM
PATH,KOPRI, THANE(E) 400 603,INDIA
Fax: 91-22-2532 4845

SPINK CONTROLS®

Phone:91-22-2532 8223/24 Email:info@spinkcontrolsindia.com
www.spinkcontrolsindia.com